

RXX00 SERIES

HIGH VOLTAGE SILICON RECTIFIER

产

品

规

格

确

认

书

R1200 THRU R2000

HIGH VOLTAGE SILICON RECTIFIER



康 比 電 子
HORNBY ELECTRONIC

REVERSE VOLTAGE: 1200 to 2000 VOLTS

FORWARD CURRENT: 0.2 to 0.5 AMPERE

FEATURES

- Low cost
- Low leakage
- Low forward voltage drop
- High current capability

MECHANICAL DATA


Case: Molded plastic, DO-41

Terminals: Axial leads, solderable per MIL-STD-202,
method 208 guaranteed

Polarity: Band denotes cathode

Mounting position: Any

Weight: 0.013ounce, 0.3gram



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	R1200	R1500	R1800	R2000	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	1200	1500	1800	2000	Volts
Maximum RMS Voltage	V _{RMS}	840	1050	1260	1400	Volts
Maximum DC Blocking Voltage	V _{DC}	1200	1500	1800	2000	Volts
Maximum Average Forward Rectified Current .375"(9.5mm) Lead Length at T _A =55	I _(AV)	0.5			0.2	Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	30				Amp
Maximum Forward Voltage at 0.5/0.2A	V _F	2.0			3.0	Volts
Maximum Reverse Current at T _A =25 at Rated DC Blocking Voltage T _A =100	I _R	5.0				uAmp
		50				
Maximum Full Load Reverse Current Average, Full Cycle .375", (9.5mm) lead length at T _L = 75		30				uAmp
Typical Junction Capacitance (Note 1)	C _J	30				pF
Operating and Storage Temperature Range	T _J , T _{stg}	-55 to +150				

NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

R1200 THRU R2000

HIGH VOLTAGE SILICON RECTIFIER



RATINGS AND CHARACTERISTIC CURVES

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS

