

***RXX00 SERIES***

***HIGH VOLTAGE SILICON RECTIFIER***

产

品

规

格

确

认

书

# R2500 THRU R5000

## HIGH VOLTAGE SILICON RECTIFIER



康 比 電 子  
HORNBY ELECTRONIC

**REVERSE VOLTAGE:** 2500 to 5000 VOLTS

**FORWARD CURRENT:** 0.2 AMPERE

### FEATURES

- Low cost
- Low leakage
- Low forward voltage drop
- High current capability

### MECHANICAL DATA


Case: Molded plastic, DO-15

Terminals: Axial leads, solderable per MIL-STD-202,  
method 208 guaranteed

Polarity: Band denotes cathode

Mounting position: Any

Weight: 0.015ounce, 0.4gram



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	R2500	R3000	R4000	R5000	Units
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	2500	3000	4000	5000	Volts
Maximum RMS Voltage	V <sub>RMS</sub>	1750	2100	2800	3500	Volts
Maximum DC Blocking Voltage	V <sub>DC</sub>	2500	3000	4000	5000	Volts
Maximum Average Forward Rectified Current .375"(9.5mm) Lead Length at T <sub>A</sub> =50	I <sub>(AV)</sub>	0.2				Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I <sub>FSM</sub>	30				Amp
Maximum Forward Voltage at 0.2A	V <sub>F</sub>	3.0	4.0	5.0		Volts
Maximum Reverse Current at T <sub>A</sub> =25 at Rated DC Blocking Voltage T <sub>A</sub> =100	I <sub>R</sub>	5.0				uAmp
Maximum Full Load Reverse Current Average, Full Cycle .375", (9.5mm) lead length at T <sub>L</sub> = 75		50				
Maximum Full Load Reverse Current Average, Full Cycle .375", (9.5mm) lead length at T <sub>L</sub> = 75		30				uAmp
Typical Junction Capacitance (Note 1)	C <sub>J</sub>	30				pF
Operating and Storage Temperature Range	T <sub>J</sub> , Tstg	-55 to +150				

### NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

R2500 THRU R5000  
HIGH VOLTAGE SILICON RECTIFIER



RATINGS AND CHARACTERISTIC CURVES

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS

