

RXX00F SERIES

HIGH VOLTAGE FAST RECOVERY RECTIFIER

产

品

规

格

确

认

书

R2500F THRU R5000F

HIGH VOLTAGE FAST RECOVERY RECTIFIER



康 比 電 子
HORNBY ELECTRONIC

REVERSE VOLTAGE: 2500 to 5000 VOLTS

FORWARD CURRENT: 0.2 AMPERE

FEATURES

- Fast switching
- Low leakage
- Low forward voltage drop
- High current capability
- High current surge
- High reliability

MECHANICAL DATA

Case: Molded plastic, DO-15


Epoxy: UL 94V-O rate flame retardant

Terminals: Axial leads, solderable per MIL-STD-202,
method 208 guaranteed

Polarity: Band denotes cathode

Mounting position: Any

Weight: 0.015ounce, 0.4gram



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	<i>R2500F</i>	<i>R3000F</i>	<i>R4000F</i>	<i>R5000F</i>	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	2500	3000	4000	5000	Volts
Maximum RMS Voltage	V _{RMS}	1750	2100	2800	3500	Volts
Maximum DC Blocking Voltage	V _{DC}	2500	3000	4000	5000	Volts
Maximum Average Forward Rectified Current .375"(9.5mm) Lead Length at T _A =50	I _(AV)	0.2				Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	30				Amp
Maximum Forward Voltage at 0.2A	V _F	4.0	5.0	6.5		Volts
Maximum Reverse Current at Rated DC Blocking Voltage T _A =25	I _R	5.0				uAmp
Maximum Full Load Reverse Current Average, Full Cycle .375", (9.5mm) lead length at T _L = 55		100				uAmp
Maximum Reverse Recovery Time (Note 1)	T _{RR}	500				nS
Operating and Storage Temperature Range	T _J , T _{stg}	-55 to +150				

NOTES:

1- Reverse Recovery Test Conditions : $I_F=.5A$, $I_R=1A$, $I_{RR}=.25A$.

R2500F THRU R5000F
HIGH VOLTAGE FAST RECOVERY RECTIFIER



RATINGS AND CHARACTERISTIC CURVES

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT





FIG. 3 - TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES1 Rise Time = 7ns max. Input Impedance = 1 megohm. 22 pF.
2. Rise Time = 10ns max. Source Impedance = 50 ohms.

