



BAS16W, BAS19W, BAS20W, BAS21W

Surface Mount Switching Diodes

Voltage 75 to 200 Volts

Power 200 mWatts

FEATURES

- Fast switching speed.
- Surface mount package ideally suited for automatic insertion
- Electrically identical to standard JEDEC
- High conductance

SOT-323



MECHANICAL DATA

- Case: SOT-323 plastic
- Terminals: Solderable per MIL-STD-202, Method 208
- Approx. weight: 0.01 grams
- Marking: A6, A8, A80, A82

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	BAS16W	BAS19W	BAS20W	BAS21W	UNITS
Reverse Voltage	V_R	75	100	150	200	V
Peak Reverse Voltage	V_{RM}	100	120	200	250	V
Rectified Current(Average), Half wave Rectification with Resistive Load and $f \geq 50$ Hz	I_o	250	200	200	200	mA
Peak Forward Surge Current, 1.0us single half sine-wave superimposed on rated load(JEDEC method)	I_{FSM}	2.0	2.5	2.5	2.5	A
Power Dissipation Derate Above 25°C	P_{tot}	200	200	200	200	mW
Maximum Forward Voltage @ $I_F=10\text{mA}$ @ $I_F=100\text{mA}$	V_F	0.855 -	- 1.0	- 1.0	- 1.0	V
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_J=25^\circ\text{C}$	I_R	1.0	0.1	0.1	0.1	μA
Typical Junction Capacitance(Notes1)	C_J	2.0	1.5	1.5	1.5	pF
Maximum Reverse Recovery (Notes2)	t_{rr}	6	50	50	50	ns
Maximum Thermal Resistance	$R_{\theta JA}$	357	375	375	375	$^\circ\text{C/W}$
Storage Temperature Range	T_J, T_{ST}	-55 to + 125				$^\circ\text{C}$

NOTE : 1. CJ at Reverse Voltage = 0. f=1MHz

2. From $I_F=10\text{mA}$ to $I_R=-1\text{mA}$. $V_R=6\text{V}$. $R_L=100\Omega$ 

BAS16W, BAS19W, BAS20W, BAS21W

Characteristic and Rating Curve

